



SMOKE ODOR CONTROL

CAPTURE PARTICULATES



HEPA 500 with carbon filter

STEP 1



9-D-9 & Double-O,
Crystal Odor Counteractant

Steps for neutralizing smoke odors caused by wild fires.

CAPTURE PARTICULATES

Install the Dri-Eaz HEPA 500 (F284) Air Scrubber with Activated Carbon Filter (F397). Smoke deposits significant amounts of particulate inside structures, and these particulates are the source of smoke odors. The HEPA 500 immediately starts capturing odor-causing particulates, and when the unit is equipped with an activated carbon filter, it will also adsorb odors. In cases of light smoke damage, using a Dri-Eaz HEPA 500 with an activated carbon filter may be all that's needed to manage the odor problem inside a structure.

STEP 1: KNOCKDOWN ODORS

With the Dri-Eaz HEPA 500 in place and operating, begin with a suppression spray of ODORx 9-D-9 or Double-O on all exposed flooring surfaces. Follow by sprinkling ODORx COC (Crystal Odor Counteractant) on all flooring surfaces. (On wood floors, place crystals in metal or paper plate.)

STEP 2



Thermo-55, Thermo-2000

FOGGERS



STEP 2: THERMAL FOG

Next turn the HEPA 500 off as well as all pilot lights on furnaces, water heaters and stoves. Use a thermal fogger and ODORx Thermo-55 (solvent based) or Thermo-2000 (water based) solutions to fog the facility. We recommend the Neutral or Cherry fragrance, both of which are very effective at suppressing wood fire odors. Allow fog to dissipate, then turn the HEPA 500 back on.

STEP 3



9-D-9 & Wall Wash

WOOD SURFACES



Woodcraft

UPHOLSTERY AND WATER WASHABLE MATERIALS



Smoke Wash

STEP 3: CLEANING

Clean all non-porous surfaces and walls with a combination of 9-D-9 and Unsmoke™ Wall Wash with Biosolv.

For finished wood surfaces use Unsmoke Woodcraft restoration cleaner.

For upholstery and water-washable materials use ODORx Smoke Wash.

Scan QR code for
PROVEN 3-STEP ODOR
REMOVAL PROCESS

