



## Filter Out (B171)

Removes filtration soil lines, toner, carbon soils, soot and other charged particle soils

FOR PROFESSIONAL USE ONLY

**APPLICATION:** Spotter

### DESCRIPTION

Filtration soils are one of the toughest problems in professional carpet cleaning. Air is forced through the carpet pile at doorways, against walls, and near HVAC vents and registers. The carpet pile acts as a filter for airborne particles, removing them from the airstream. These particles cling tightly to the carpet fibers through electrostatic and mechanical attraction. Over time this can form a tough soil that is a real challenge to remove . . .UNTIL NOW!

**Filter-Out** removes air filtration soil lines along walls, under doors and near heating and air conditioning vents, where airborne particles are filtered out and deposited in carpet pile. Exclusive Prochem formulation technology defeats the particle charge attraction and allows the soil to be extracted away. Solves problems that you couldn't solve before.

**Filter-Out** also can remove other types of tough spots, including copier, printer and fax machine toner spills, carbon-containing soils, carbon soot, and other charged particle soils which are strongly attracted to fibers.

### FEATURES

- Removes filtration soil lines from carpet along walls and doorways.
- Extracts dry toner spills near copiers, fax machines, laser printers
- Rinse-extract with water or Prochem's All Fiber Rinse solution.
- Available ready-to-use in quart bottles with convenient applicator cap.

### WHERE TO USE

Residential and commercial carpets with filtration soil lines. Removes dry toner spills near photocopiers, fax machines and laser printers. Soot and other dry carbon soils on carpet or hard surfaces.

**USE DILUTION:** Ready-to-use - No mixing necessary.

### USE DIRECTIONS:

1. Pre-vacuum thoroughly to remove loose soil, especially dry toner.
2. Apply Filter-Out to saturate fibers in soiled areas. Allow 3-5 minutes dwell time to loosen soil. Agitate with a soft brush or groomer to help break loose tough spots.
3. Extract completely using hot water or All Fiber Rinse solution. Repeat if needed.
4. Lightly brush or groom to align fibers.

### USAGE TIPS:

- Pre-vacuum toner spills repeatedly to remove as much loose toner as possible before wet cleaning. Use a vacuum hose attachment or a vacuum without a beater bar to avoid spreading toner.
- Always rinse-extract to remove soil and residues.
- Apply a carpet protector such as FourGuard to restore soil and stain resistance.
- Filter-Out is not recommended for use on upholstery fabrics.

Additional tips for spot and stain removal are available in our Tech Tips blog at [LegendBrandsCleaning.com](http://LegendBrandsCleaning.com)

**ADDITIONAL REFERENCES** available at [LegendBrandsCleaning.com](http://LegendBrandsCleaning.com)

- Cleaning system guides
- Product User Guides
- Safety Data Sheets
- Product labels
- Tech Tips blog

Filter Out Technical Data	
Color	Light green
Odor	Floral
Appearance	Clear liquid
VOCs	See Safety Data Sheet
pH of ready-to-use:	10.0 – 10.5
Reorder numbers:	
101023 (8.695-056.0 – B171-12): Twelve 1 quart / 0.9 L bottles	

### Boost your skills and knowledge with Legend Brands Education!

Taught by leading experts in the cleaning and restoration industry, Legend Brands Education courses enhance your knowledge of cleaning and restoration processes and improve your skills and boost your profitability. Courses are hosted online, at distributor locations, and at in hands-on training facilities. For current offerings, visit [LegendBrandsEducation.com](http://LegendBrandsEducation.com) or call 800-932-3030.