

PRORESTORE
PRODUCTS

Electro-Gen Thermal Fogger

For powerful, versatile fogging. As a thermal fogger, this unit produces extremely fine particle size that mimics the behavior of smoke, delivering odor control deep into cracks, crevices and cavities. Use with [ODORx Thermo-55](#) solvent-based formulations. Or, detach the heater barrel for use as a cold sprayer with water-based products or ProRestore's [Disinfectant Spray Plus](#) antimicrobial products. Always follow fogging product label instructions exactly.

FEATURES

- Produces a true "dry fog" with a very small particle size similar to smoke for deep penetration.
- Virtually eliminates the drips and streaks associated with conventional misters and foggers.
- Can be used as an electric sprayer to apply solvent- or water-based chemicals for deodorizing. Simply remove the heater barrel for this function.

SIZES • OPTIONS

- **116257 (102257000)**: One 110V unit
- **101277000**: One 220V unit



SPECIFICATIONS

- **Output spraying**: 1 oz. (30 ml) per minute
- **Output fogging**: 1,000 cu. ft. (28 cu. m.) per minute
- **Fogging**: Hot: 13.5 microns
Cold: 115 microns
- **Amps**: 8A (230V = 4 amps)
- **Volts**: 115V
- **Power**: 900W
- **Motor**: Electro-mechanical vibrator operating at 7,200 strokes per minute
- **Pump**: Displacement type
- **Heating element** : Thermostatically controlled
- **Solution reservoir**: Spun aluminum 3 qt. / 2.8 L capacity
- **Operating temperature**: 450°F–525°F | 232°C–274°C