



NEW! DRIFORCE[®] XL HIGH-PERFORMANCE QUIETER DRYING SYSTEM



BUILT IN USA
WITH GLOBALLY SOURCED MATERIALS

The DriForce XL deploys more than 2X the static pressure to speed dry high-risk areas:

- Walls and ceilings, especially with watertight finishes
- Double and triple-sheeted fire walls, party walls, sound barriers and in-wall insulation
- Walls behind cabinets and fixtures
- Hardwood floors

Choose positive airflow to direct warm, dry air into cavities to accelerate drying OR negative vacuum to draw moist air out of wall cavities and floor flutes.

Superior Build, Premium Performance

- **Consistent high-power airflow** - Restoration-optimized Variable Frequency Drive in Airtech regenerative blower built for rugged restoration use - and no factory recalibration required
- **High performance, low amp draw** - Operates on standard 15-amp circuit
- **Sturdy, long-life build** - Open air design enhances component cooling for extended life expectancy - and even quieter than enclosed units
- **Broadly compatible** - Connects to Dri-Eaz Air Drying System and Rescue Mats and similar systems.
- **Easy transport** - Rugged frame and large wheels, nests securely for stacking and storage

Order from your dealer today!



ITEM	#124159
RATED AIRFLOW	130 CFM 221 M3/H
VACUUM (MAX.)	84 IN. H2O 20.9 KPA
STATIC PRESSURE (MAX)	88 IN. H2O 21.9 KPA
DIMENSIONS (W×H×D)	20.8 × 26.3 × 18.4 IN. 52.3 × 66.8 × 46.8 CM
WEIGHT (W/ATTACHMENTS)	86.9 LBS. 39.4 KG
AMPS/VOLTS/FREQ.	12A / 115V / 60HZ
POWER CORD	25 FT. 7.6 M HOSPITAL GRADE LIGHTED NEMA 5-15P
SOUND LEVEL	71 DB
SAFETY	ETL LISTED TO UL 507 AND CSA C22.2 NO. 113:15
XACTIMATE	WTR WFI

Industry-leading 3-YEAR LIMITED WARRANTY on key components!